







ROHS

Compatible



NOTE:

1.MATERIAL SPECIFICATION:

1.HOUSING:HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0.

2.CONTACTS: COPPER ALLOY

3.MID PLATE: STAINLESS STEEL

2.PLATING SPECIFICATION:

2-1.CONTACTS:

Ni 50u" MIN. UNDER PLATED OVER ALL.

ALL PLATED ON THE FUNCTIONAL AREA OF CONTACT.

(GOLD PLATING THICKNESS FOLLOW THE P/N)

GOLD FLASH PLATING ON SOLDER AREA

2-2.FRONT SHELL:

Ni 30u" MIN. UNDER PLATED OVER ALL.

3. MECHANICAL PERFORMANCE

3-1.INSERTION FORCE: 0.5~2.0kgf.

3-2.REMOVAL FORCE: 0.8kqf~2.0kqf.

3-3.DURABILITY: 10000 CYCLES.

4.ELECTRICAL PERFORMANCE.

4-1. CURRENT RATING: 5A

VOLTAGE RATING: 20V

4-2.INSULATION RESISTANCE: 100MΩ MIN

4-3.DIELECTRIC WITHSTAND VOLTAGE.AC 100V FOR 1 MINUTE.

4-4. LOW CONTACT RESISTANCE: INITIAL 40MΩ

AFTER 50MΩ

5. ENVIRONMENTAL PERFORMANCE:

OPERATING TEMPERATURE: $-30^{\circ}\text{C}\sim+80^{\circ}\text{C}$.

6.IR REFLOW:

THE PEAK TEMPERATURE ON THE BOARD SHALL

BE MAINTAINED FOR 10 SECONDS AT 260°C.

U5 088- 16P x 7.35L

名称 流水号 PIN位 N;母座 L;长度

DESIGN	Li Jinwei	SCALL		 TOLERANCE	DRAWG NO. U5088-16PN7.35L
DRAWING	Wu Qifa	UNIT	mm		
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297		X.X ±0.30 X.°±2° .XX ±0.20 .X° ±1° .XXX ±0.10 .XX°±0.5°
APPROVAL	Liu Xiaohong	DATE	2020-06-10		TITLE: 16P 板上型四脚插板SMT 7.35L




广东宏煜盛电子科技有限公司

Guangdong Hongyusheng Electronic Technology Co., Ltd.

BXBL


TEL:0752-6632356 <https://www.hystypec.com>

ROHS
Compatible




USB TYPE-C PIN ASSIGNMENTS


PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND



RECOMMEND P.C.B LAYOUT(COMPONENT SIDE)
TOLERANCE FOR PCB LAYOUT IS ± 0.05

DESIGN	Li Jinwei	SCALL		 TOLERANCE X.X ±0.30 X.°±2° .XX ±0.20 X.° ±1° .XXX ±0.10 .XX°±0.5°	DRAWG NO.	 广东宏煜盛电子科技有限公司 Guangdong Hongyusheng Electronic Technology Co., Ltd. TEL:0752-6632356 https://www.hystypec.com
DRAWING	Wu Qifa	UNIT	mm		U5088-16PN7.35L	
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297		TITLE:	
APPROVAL	Liu Xiaohong	DATE	2020-06-10		16P 板上型四脚插板SMT 7.35L	

ROHS
Compatible




NOTES


1.帶子引導長度
LEAD TAPE LENGTH

出料方向
PULL OUT DIRECTEON

出料方向
PULL OUT DIRECTEON




2.上帶剝力為: 0.1~1.3N(10.2gf~130gf)
PEELING OFF FORCE OF TOP TAPE: 0.1~1.3N(10.2gf~130gf)
出貨運輸過程中一定注意:
THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT:
卷帶在運輸過程中不能散開
PEELING OFF SHOULD NOT BE ALLOWED DURING TRANSPORTATION



TAPE & REEL 14 PCS


1 REEL
= 1000 PCS



BOX

DIMENSIONS:
33.5X33.5X30.5

LABEL



1 CARTON
=14 REELS
=14000 PCS

包裝明細表 (The detail of the packing) Carton						
產品料號 (Product No.)	包裝容量 (Packing Capacity)			重量 Weight (Kg)		
	pcs/box	boxes/Carton	Pcs/Box	N.W./Pcs	N.W./Box	G.W./Box
U5088-16PN7.35L	1000	14	14000	—	—	—

DESIGN	Li Jinwei	SCALL		 TOLERANCE X.X ±0.30 X.°±2° .XX ±0.20 .X°±1° .XXX ±0.10 .XX°±0.5°	DRAWG NO. U5088-16PN7.35L	 广东宏煜盛电子科技有限公司 Guangdong Hongyusheng Electronic Technology Co., Ltd. TEL:0752-6632356 https://www.hystypec.com
DRAWING	Wu Qifa	UNIT	mm		TITLE: 16P 板上型四脚插板SMT 7.35L	
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297			
APPROVAL	Liu Xiaohong	DATE	2020-06-10			