





ROHS

Compatible



SECTION B-B
SCALE 1:1





SECTION A-A
SCALE 1:1

NOTE:

1. MATERIAL SPECIFICATION:
1. HOUSING: HIGH TEMPERATURE RESISTANT PLASTIC, UL94 V-0.
2. CONTACTS: COPPER ALLOY
3. MID PLATE: STAINLESS STEEL
2. PLATING SPECIFICATION:
2-1. CONTACTS:
Ni 50u" MIN. UNDER PLATED OVER ALL.
Au PLATED ON THE FUNCTIONAL AREA OF CONTACT.
(GOLD PLATING THICKNESS FOLLOW THE P/N)
GOLD FLASH PLATING ON SOLDER AREA
- 2-2. FRONT SHELL:
Ni 30u" MIN. UNDER PLATED OVER ALL.
3. MECHANICAL PERFORMANCE,
3-1. INSERTION FORCE: 0.5~2.0kgf.
3-2. REMOVAL FORCE: 0.8kgf~2.0kgf.
3-3. DURABILITY: 10000 CYCLES.
4. ELECTRICAL PERFORMANCE,
4-1. CURRENT RATING: 5A
VOLTAGE RATING: 20V
4-2. INSULATION RESISTANCE: 100MΩ MIN
4-3. DIELECTRIC WITHSTAND VOLTAGE, AC 100V FOR 1 MINUTE.
4-4. LOW CONTACT RESISTANCE: INITIAL 40MΩ
AFTER 50MΩ
5. ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -30℃~+80℃.
6. IR REFLOW:
THE PEAK TEMPERATURE ON THE BOARD SHALL
BE MAINTAINED FOR 10 SECONDS AT 260℃.
- | | | | | | |
|----|------|------|------|------|-------|
| U5 | 096- | 16P | x | 1.0G | 7.35L |
| ↓ | ↓ | ↓ | ↓ | ↓ | ↓ |
| 名称 | 流水号 | PIN位 | N:母座 | G:垫高 | L:长度 |

DESIGN	Li Jinwei	SCALL		 TOLERANCE X.X ±0.30 X.°±2° .XX ±0.20 X.°±1° .XXX ±0.10 .XX°±0.5°	DRAWG NO.	U5096-16PN1.0G7.35L	 东莞市宏煜盛实业有限公司 Dongguan hongyusheng Industry Co., Ltd TEL: 0769-81230179 https://www.hystypec.com
DRAWING	Wu Qifa	UNIT	mm		TITLE:		
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297			16P 板上四脚插板SMT 垫高1.0mm 7.35L	
APPROVAL	Liu Xiaohong	DATE	2020-06-10				


ROHS
Compatible



USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME
A1	GND
A4	VBUS
A5	CC1
A6	Dp1
A7	Dn1
A8	SBU1
A9	VBUS
A12	GND


PIN NUMBER	SIGNAL NAME
B12	GND
B9	VBUS
B8	SBU2
B7	Dn2
B6	Dp2
B5	CC2
B4	VBUS
B1	GND



RECOMMEND P.C.B LAYOUT(COMPONENT SIDE)
TOLERANCE FOR PCB LAYOUT IS ± 0.05

DESIGN	Li Jinwei	SCALL			DRAWG NO.	东莞市宏煜盛实业有限公司 Dongguan hongyusheng Industry Co., Ltd TEL: 0769-81230179 https://www.hystypec.com	
DRAWING	Wu Qifa	UNIT	mm		TOLERANCE		U5096-16PN1.0G7.35L
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297		X.X ±0.30 X.°±2° .XX ±0.20 .X° ±1° .XXX ±0.10 .XX°±0.5°		TITLE:
APPROVAL	Liu Xiaohong	DATE	2020-06-10		16P 板上四脚插板SMT 垫高1.0mm 7.35L		


ROHS
Compatible




NOTES

1.帶子引導長度
LEAD TAPE LENGTH

出料方向
PULL OUT DIRECTION




2.上帶 剝力力為: 0.1~1.3N(10.2gf~130gf)
PEELING OFF FORCE OF TOP TAPE: 0.1~1.3N(10.2gf~130gf)
出貨運輸過程中一定注意:
THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT:
卷帶在運輸過程中不能散開
PEELING OFF SHOULD NOT BE ALLOWED DURING TRANSPORTATION




TAPE & REEL 14 PCS

1 REEL
= 1000 PCS



BOX

DIMENSIONS:
33. 5X33. 5X30. 5



1 CARTON
=14 REELS
=10000 PCS

包裝明細表 (The detail of the packing) Carton

產品料號 (Product No.)	包裝容量 (Packing Capacity)			重量 Weight (Kg)		
	pcs/box	boxs/Carton	Pcs/Box	N.W./Pcs	N.W./Box	G.W./Box
U5096-16PN1.0G7.35L	1000	14	14000	—	—	—

DESIGN	Li Jinwei	SCALL			DRAWG NO. U5096-16PN1.0G7.35L	
DRAWING	Wu Qifa	UNIT	mm			
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297			
APPROVAL	Liu Xiaohong	DATE	2020-06-10			

TOLERANCE
X.X ±0.30 X.°±2°
.XX ±0.20 .X°±1°
.XXX ±0.10 .XX°±0.5°

TITLE:
16P 板上四脚插板SMT 墊高1.0mm 7.35L



东莞市宏煜盛实业有限公司
Dongguan hongyusheng Industry Co., Ltd
TEL: 0769-81230179 <https://www.hystypec.com>