









ROHS
Compatible



SPECIFICATION:

- 1.CURRENT RATING: 3.0 A
- 2.VOLTAGE RATING: 5.0 V
- 3.VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX
SHIELD: 50mΩ/MAX
LLCR MAX. CHANGE OF ALL PINS: 10mΩ
- 4.INSULATION RESISTANCE: 100MΩ MIN
- 5.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1MINUTE
- 6.INSERTION FORCE: 0.5~2.0kgf
- 7.UNMATING FORCE: 0.8~2.0kgf
- 8.DURABILITY: 10000 CYCLES
- 9.OPERATING TEMPERATURE: -25°C~+85°C
- 10.THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C
11. WATERPROOF:IP66.

U5 370- 08P x 0.78C 6.7L x
名称 流水号 PIN位 N;母座 C;沉板 L;长度 F;防水



A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
				CC1	D+	D-		VBUS			GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND			VBUS				CC2				





NO.	PARTS	MATERIAL	REMARKS
1	SHELL	ZN ALLOY	NI PLATED
2	MID PLATE	STAINLESS STEEL	SUS304 NO PLATED
3	HOUSING	HIGH TEMPERATURE PLASTIC	LCP BLACK UL94V-0
4	CONTACT	COPPER ALLOY(C5191)	Au PLATING ON CONTACT AREA
5	RING	SILICON	

DESIGN	Li Jinwei	SCALL			DRAWG NO.	
DRAWING	Wu Qifa	UNIT	mm		TOLERANCE	U5370-08PN0.78C6.7LF
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297		X.X ±0.30 X.°±2° .XX ±0.20 .X°±1° .XXX ±0.10 .XX°±0.5°	TITLE:
APPROVAL	Liu Xiaohong	DATE	2020-06-10			防水8P 两脚贴片SMT 沉板0.78m 6.7L IP66



广东宏煜盛电子科技有限公司
Guangdong Hongyusheng Electronic Technology Co., Ltd.
TEL:0752-6632356 <https://www.hystypec.com>

ROHS
Compatible



	REEL	CARTON
CONNECTOR (PCS)	1000	10000

DESIGN	Li Jinwei	SCALL			DRAWG NO.	U5370-08PN0.78C6.7LF	
DRAWING	Wu Qifa	UNIT	mm		TOLERANCE		TITLE:
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297		X.X ±0.30 X.°±2° .XX ±0.20 .X°±1° .XXX ±0.10 .XX°±0.5°		防水8P 两脚贴片SMT 沉板0.78m 6.7L IP66
APPROVAL	Liu Xiaohong	DATE	2020-06-10				



广东宏煜盛电子科技有限公司

Guangdong Hongyusheng Electronic Technology Co., Ltd

TEL:0752-6632356 <https://www.hystypec.com>





广东宏煜盛电子科技有限公司
Guangdong Hongyusheng Electronic Technology Co., Ltd.
TEL: 0752-6632356 <https://www.hystypec.com>